

Kemiko Concrete Products
PO Box 1109
Leonard, Texas 75452
Phone (903) 587-3708
Fax (903) 587-9038
Web Site www.kemiko.com
E-Mail sales@kemiko.com

November 2002

Product Guide Specification

Specifier Notes: This product guide specification is written according to the Construction Specifications Institute (CSI) 3-Part Format, including *MasterFormat*, *SectionFormat*, and *PageFormat*, contained in the *CSI Manual of Practice*.

The section must be carefully reviewed and edited by the Architect to meet the requirements of the project and local building code. Coordinate this section with other specification sections and the drawings.

Delete all "Specifier Notes" when editing this section.

SECTION 09695

FLOOR WAX

Specifier Notes: This section covers Kemiko Stone Tone Wax for use on interior porous floor surfaces unaffected by mineral spirits, such as concrete, unglazed brick, unglazed tile, flagstone, and unsealed wood.

Consult Kemiko for assistance in editing this section for the specific application.

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Wax for interior [concrete] [unglazed brick] [unglazed tile] [flagstone] [unsealed wood] floor surfaces.

1.2 RELATED SECTIONS

Specifier Notes: Edit the following list of related sections as required for the project. List other sections with work directly related to this section.

- A. Section 03300 - Cast-in-Place Concrete.
- B. Section 09300 - Tile: Unglazed floor tile.

- C. Section 09630 - Masonry Flooring: Unglazed brick flooring, flagstone flooring.
- D. Section 09640 - Wood Flooring: Unsealed wood flooring.

1.3 SUBMITTALS

- A. Comply with Section 01330 - Submittal Procedures.
- B. Product Data: Submit manufacturer's product data, including surface preparation and application instructions.
- C. Maintenance Instructions: Submit manufacturer's maintenance and cleaning instructions.

1.4 DELIVERY, STORAGE, AND HANDLING

- A. Delivery: Deliver materials to site in manufacturer's original, unopened containers and packaging, with labels clearly identifying manufacturer and product name.
- B. Storage: Store materials in a clean, dry area indoors in accordance with manufacturer's instructions. Keep containers sealed until ready for use. Keep away from ignition sources. Do not allow to freeze.
- C. Handling: Protect materials during handling and application to prevent damage or contamination.

1.5 ENVIRONMENTAL REQUIREMENTS

- A. Do not apply wax when air or surface temperature is below 55 degrees F.

PART 2 PRODUCTS

2.1 MANUFACTURER

- A. Kemiko Concrete Products, PO Box 1109, Leonard, Texas 75452. Phone (903) 587-3708. Fax (903) 587-9038. Web Site www.kemiko.com. E-Mail sales@kemiko.com.

2.2 FLOOR WAX

- A. Floor Wax: Kemiko Stone Tone Wax.
 1. Petroleum wax.
 2. Nonyellowing.
 3. Fast drying.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Examine surfaces to receive wax. Notify Architect if surfaces are not acceptable. Do not begin surface preparation or application until unacceptable conditions have been corrected.

3.2 SURFACE PREPARATION

Specifier Notes: Surface preparation will vary depending on the material and condition of the floor surface. Consult Kemiko for additional information.

- A. Prepare surface in accordance with manufacturer's instructions.
- B. Ensure surface is clean, dry, and free from dirt, dust, stain residue, and other surface contaminants.

3.3 APPLICATION

- A. Apply and buff wax in accordance with manufacturer's instructions at locations indicated on the drawings.
- B. Keep material containers closed when not in use to avoid contamination.

3.4 PROTECTION

- A. Protect waxed floor surface from damage during construction.

END OF SECTION